JOB No. 8717

FILE No. R18526-F

DESCRIPTION

LOT 45, ANDREWS PLANTATION II, AS PER PLAT RECORDED IN PLAT BOOK 29, PAGES 1 THRU 5 OF THE PUBLIC RECORDS OF BAY COUNTY, FLORIDA.

SURVEYOR'S NOTES:

THIS IS A BOUNDARY SURVEY WITH THE LOCATION OF ABOVE GROUND FIXED IMPROVEMENTS IN THE IMMEDIATE VICINITY OF THE ABOVE DESCRIBED PARCEL BOUNDARY ONLY. NO ATTEMPT WAS MADE TO INVESTIGATE THE LOCATION OF UNDERGROUND UTILITIES, FOUNDATIONS, OR OTHER IMPROVEMENTS, IF ANY

THE LEGAL DESCRIPTION SHOWN HEREON WAS FURNISHED BY CLIENT.

THE UNDERSIGNED SURVEYOR HAS NOT BEEN PROVIDED A CURRENT TITLE OPINION OR ABSTRACT OF MATTERS AFFECTING THE TITLE OR BOUNDARY OF THE SUBJECT PROPERTY. IT IS POSSIBLE THAT THERE ARE DEEDS OF RECORD, UNRECORDED DEEDS, EASEMENTS OR OTHER INSTRUMENTS THAT COULD AFFECT THE BOUNDARIES.

THE BEARINGS AS SHOWN HEREON ARE BASED ON PLAT BEARING OF SOUTH 03'00'18" WEST ALONG CENTERLINE OF CASON CIRCLE FROM THE INTERSECTION OF CASON DRIVE SOUTH TO THE P.C. NEAR LOT 40 AND REFERENCED TO GEODETIC NORTH BASED ON THE FLORIDA STATE PLANE COORDINATES SYSTEM, NORTH ZONE, NAD 1983/99, U.S. SURVEY FEET. DATUM ESTABLISHED USING FLORIDA PERMANENT REFERENCE NETWORK.

THE MINIMUM HORIZONTAL ACCURACY FOR THIS SUBURBAN SURVEY PREPARED IN ACCORDANCE WITH THE STANDARDS OF PRACTICE SET FORTH THE BOARD OF PROFESSIONAL SURVEYORS AND MAPPERS IN CHAPTER 5J-17.050-.052 OF THE FLORIDA ADMINISTRATION CODE, IS ONE PART IN 7,500. THE MAP AND MEASUREMENT METHODS USED FOR THIS SURVEY MEET OR EXCEED THIS REQUIREMENT. THE DIMENSIONS SHOWN HEREON ARE IN FEET AND DECIMALS THEREOF

A COMPARISON BETWEEN RECORDED DIRECTIONS AND DISTANCES AND FIELD MEASURED DIRECTIONS AND DISTANCES WERE MADE. THE RECORD MEASUREMENTS ARE SHOWN IN PARENTHESES.

THIS SURVEY DOES NOT DETERMINE OWNERSHIP OF THE LANDS SHOWN

VERTICAL INFORMATION SHOWN HEREON IS REFERENCED TO THE STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION CONTROL, BEING A CONCRETE MONUMENT STAMPED "W290" HAVING A PUBLISHED ELEVATION OF 32.43 NAVD BB DATUM.

A REVIEW OF THE FLOOD INSURANCE RATE MAP FOR BAY COUNTY, FLORIDA, MAP No. 12005C0323H, REVISED JUNE 2, 2009 INDICATES THAT THE PARCEL SHOWN HEREON IS WITHIN ZONE X, AS PER LOMR CASE No.: 20-04-2912P, EFFECTIVE DATE AUGUST 16, 2021.

THE SURVEY MAP(S) AND REPORT ARE NOT VALID WITHOUT THE SIGNATURE AND ORIGINAL RAISED SEAL OF THE FLORIDA LICENSED SURVEYOR AND MAPPER WHO PREPARED IT. ADDITIONS OR DELETIONS TO SURVEY MAP(S) OR REPORT BY OTHER THAN THE SIGNING PARTY IS PROHIBITED WITHOUT WRITTEN CONSENT OF THE SIGNING PARTY.

SKIPPER OR RUTHEREORD BY SPPER PROFESSIONAL SURVEYOR & TAPPER FLORIDA LICENSIA

FEATURES SHOWN BY SYMBOL AS INDICATED IN THE LEGEND ARE NOT TO

THE FORMATTED CERTIFICATION IS FOR: D.R. HORTON, INC.

(1)

0

0

ШШ

02.

ZZ

C. RUTHER DE LES 3961 CORRECT DO SE TRUE AND CORRECT DO SE TRUE AND CORRECT DO SE THE DATE SURVEYED. CERTIFICATE

I HEREBY CERTIFY THE SURVEY HEREON TO BE TRUE AND CORRECT!

THE BEST OF MY KNOWLEDGE AND BELLET AS OF THE DATE SURVEY.

7-31-2023 DATE REVISED

7-28-2023 DATE OF SURVEY

25.0'

PLATTED SETBACK

DENOTES

DENOTES FD. 5/8" IRON ROD & CAP No. LB 6745-

LΩ

4

55. CONC. DRIVE 33 20.0' 020 SO 27.9" 29.99 (30.00')S 87'07'22" E - 125.05" (S 87'10'46" E - 125.00')

SET 5/8" IRON ROD & CAP No. LS 3961 ON A 2' OFFSET

SYMBOLS & ABBREVIATIONS MORE OR LESS
DEGREES
MINUTES OR FEET
SECONDS OR INCHES
POINT OF COMMENCEMENT
POINT OF BEGINNING
POINT OF CURVATURE
POINT OF TANGENCY
POINT OF REVERSE CURVATURE
POINT OF COMPOUND CURVATURE MON. R.O.W. POINT OF COMPOUND CURVATURE NORTH SOUTH WEST TOWNSHIP LS F.B. EFB F.F. OFFICIAL RECORDS BOOK PROFESSIONAL LAND SURVEYOR

PUBL

USE ÄS

PUBLIC

29 6 Z

P.O.C. P.O.B. P.C. P.T. P.R.C. P.C.C.

SEC.

O.R.B. P.L.S. PG.

JACK

6.5g

CORNER CONCRETE RIGHT OF WAY STATE ROAD COUNTY ROAD BUILDING
ELEVATION
DELTA/CENTRAL ANGLE
ARC LENGTH CHORD OVERHEAD UTILITIES CENTERLINE
LICENSED BUSINESS
LICENSED SURVEYOR FIELD BOOK
ELECTRONIC FIELD BOOK
FINISHED FLOOR

Ö

(N 87'10'46" W - 125.00')

N 8712'10" W - 124.85'

122.85